

## Egg Printing Inkjet Printer



Specification	Controller : 210*135*37mm (H*W*D) / 8.3*5.3*1.46 inch Printhead : 113*133*55mm (H*W*D) / 4.5*5.2*2.15 inch (including spring mechanism)
Language	Chinese, English, Japanese, French, German, Spanish, Portuguese and Russian
Resolution	50~600DPI
Counters	Can be set in Series No, Carton No, Pallet No, etc
Printable heights (mm)	1~76.2mm
Printing speed	0-60 m/min (300 DPI) 0-30 m/min(600 DPI)
Conveyor speed	Can be set, auto-calculated or use external synchronizer
Barcode	UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, EAN128, PDF417, DATAMATRIX, QR
Date format	Production date, expiry date with several formats for option
User management	3 level operating authorization (operator, technician, administrator)
Database	PC software supports MS Excel, MS Access, SQL2000, SQL2005, SQL2008 etc. database formats
Data Source	Standard RS-232 and ethernet port, easy for integration
Screen	1) 7 inch 800*480 resolution color LCD touch screen 2) Brand new operation interface, easy to learn and operate 3) Printer can work independently without PC software
Port	1) Ethernet: support PC software communication protocol SDK. 2) USB2.0: Support U-Disk 3) DB15: For external devices like photocell, synchronizer or alarm kit
Ink management	Identify ink type automatically and use the best printing parameters Original HP ink cartridge guaranteed Automatic measuring system for ink consumption
Installation	Professional installation bracket
Power Input	AC 100V-240V/50-60HZ, 90W (Dedicated AC adaptor)
Certificate	CE, FCC



### Independent & Stretchable Printhead

Printhead can stretch from 0-10mm according to egg surface.



### Data Copy

One head's message can be copied to others, to avoid repetitive work.



### Free selection of Printhead(s)

According to different application, user can select different printheads quantity.



### Professional Installation Bracket

Professional bracket, easy to install and operate.

